

SAFETY DATA SHEET

<u>SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE</u> <u>AND OF THE COMPANY/UNDERTAKING</u>

1.1 Product identifier

Product Name METSO BEADS® 2048

Sodium metasilicate

Alternative names Sodium metasilicate (anhydrous)

CAS No. 6834-92-0 EINECS No. 2299129

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified use(s)

General purpose industrial chemical for use in a wide range of

applications.

Complexing agent; Corrosion inhibitor; Flame retardant or fire preventing agent; Flotation agent; pH Regulating agent;

Viscosity control agent

See also Annex to the extended Safety Data Sheet.

Uses advised against None known.

1.3 Details of the supplier of the safety data sheet

Company Identification PQ Corporation

P.O. Box 840 Valley Forge PA 19482 USA

Telephone: +1 610-651-4200
E-Mail (competent person) sds.uk@pqcorp.com

1.4 Emergency telephone number

Emergency Phone No. +1 800-424-9300

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

GHS Classification Skin Corr. 1B / Eye Dam. 1

STOT SE 3 Met. Corr. 1

EC Classification CORROSIVE

Hazards summary Alkaline. Causes burns.

Irritating to respiratory system.

May cause permanent damage to eyes. Can etch glass if not

promptly removed.

2.2 Label elements

Hazard pictogram(s)



- en -

Signal word(s) Danger

Revision: GHS v1.1 Date of Issue: 04/2013

Date Previous Issue: 5/22/2009

Ref: 01-1-1-00-000 PQUS - GHS - 3 Page: 1 of 7



Hazard statement(s) H314: Causes severe skin burns and eye damage.

H335: May cause respiratory irritation. H290: May be corrosive to metals.

Precautionary statement(s) P261: Avoid breathing dust.

P262: Do not get in eyes, on skin, or on clothing. P280: Wear protective gloves/protective clothing/eye

protection/face protection.

P301+P330+P331: IF SWALLOWED: rinse mouth. Do NOT

induce vomiting.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

CORROSIVE EC Classification

Hazard Symbol

Risk Phrases R34: Causes burns.

R37: Irritating to respiratory system.

Safety Phrases S1/2: Keep locked up and out of the reach of children.

S13: Keep away from food, drink and animal feedingstuffs.

S24/25: Avoid contact with skin and eyes.

S36/37/39: Wear suitable protective clothing, gloves and

eye/face protection.

S45: In case of accident or if you feel unwell, seek medical

advice immediately (show the label where possible).

Not applicable. 2.3 Other hazards

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Regulation (EC) No. 1272/2008 (CLP)

Ingredient(s)	%W/W	CAS No.	EINECS No. /	Hazard symbol(s) and
			REACH Registration	hazard statement(s)
Silicic acid, disodium	100	6834-92-0	2299129	H314 : Skin Corr. 1B
salt; Disodium				Eye Dam. 1 ;
metasilicate				H335 : STOT SE 3 ;
				H290 : Met. Corr. 1 ;

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

Eye Contact Irrigate with eyewash solution or clean water, holding the eyelids

apart, for at least 15 minutes. Obtain immediate medical

attention.

Skin Contact Wash affected skin with plenty of water. Continue to wash the

affected area for at least 15 minutes. Obtain medical attention.

Revision: GHS v1.1 Ref: 01-1-1-00-000 - en -Date of Issue: 04/2013 PQUS - GHS - 3 Date Previous Issue: 5/22/2009 Page: 2 of 7



Remove patient from exposure, keep warm and at rest. Obtain Inhalation

immediate medical attention.

Do not induce vomiting. Wash out mouth with water and give Ingestion

200-300 ml (half a pint) of water to drink. Obtain immediate

medical attention.

4.2 Most important symptoms and effects, both acute and

delaved

4.3 Indication of any immediate medical attention and special

treatment needed

Alkaline. Causes burns. Irritating to respiratory system.

May cause permanent damage to eyes. Obtain immediate medical attention.

SECTION 5: FIRE-FIGHTING MEASURES

5.1 Extinguishing media

Suitable Extinguishing Media Unsuitable extinguishing Media

5.2 Special hazards arising from the substance or mixture

5.3 Advice for fire-fighters

Compatible with all standard fire fighting techniques.

None known.

Not applicable. Inorganic powder or granules. Non-combustible.

None

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

6.2 Environmental precautions

6.3 Methods and materials for

containment and cleaning up

6.4 Reference to other sections

Wear suitable protective clothing. Wear eye/face protection. An approved dust mask should be worn if dust is generated during handling.

Do not allow to enter drains, sewers or watercourses. Advise Authorities if spillage has entered water course or sewer or has

contaminated soil or vegetation.

Caution - spillages may be slippery. Avoid generation of dust. Sweep or preferably vacuum up and collect in suitable containers

for recovery or disposal.

See also Section 8.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling Avoid contact with eyes, skin and clothing.

Avoid generation of dust.

Emergency shower and eye wash facilities should be readily

available.

See Also Section 8.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed and dry. In case of high humidity or storage for extended periods of time, use plastic bags to enclose

product containers to avoid caking. Unsuitable containers: Aluminium

See Also Section 10.

7.3 Specific end use(s) Not available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Revision: GHS v1.1 Ref: 01-1-1-00-000 - en -Date of Issue: 04/2013 PQUS - GHS - 3 Date Previous Issue: 5/22/2009 Page: 3 of 7



SUBSTANCE.	Occupational Exposure Limits		
Disodium metasilicate	No Occupational Exposure Limit assigned.		
	An exposure limit of 2 mg/m3 (15 min TWA) is recommended by analogy		
	with sodium hydroxide (UK EH40).		

Wear protective equipment to comply with good occupational 8.2 Exposure controls hygiene practice. Do not eat, drink or smoke at the work place.

8.2.1 Appropriate engineering controls

Engineering methods to prevent or control exposure are preferred. Methods include process or personnel enclosure, mechanical ventilation (dilution and local exhaust), and control of process conditions.

8.2.2 Personal Protection

Respiratory protection

Avoid inhalation of dusts. Wear suitable respiratory protective equipment if working in confined spaces with inadequate ventilation or where there is any risk of the exposure limits being exceeded. Advice on respiratory protective equipment is given in the HSE (Health and Safety Executive) publication HS(G)53.

Eye/face protection Chemical goggles (EN 166).

Wear suitable protective clothing and gloves. PVC or rubber Skin protection

gloves. For example EN374-3. Wear suitable overalls.

8.2.3 Environmental Exposure

Controls

The primary hazard of sodium silicate is the alkalinity. Avoid generation of dust. Avoid release to the environment.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance Powder. Granules. White.

Odour Odourless. Odour Threshold (ppm) Not applicable.

pH (Value) Strongly alkaline. Approx 14

Freezing Point (°C) Not applicable.

Melting Point (°C) 1089

Oxidising Properties

Boiling Point (°C) Not applicable. Flash Point (°C) [Closed cup] Not applicable. Evaporation rate Not applicable. Flammability (solid, gas) Not applicable. Not applicable. **Explosive Limit Ranges** Vapour Pressure (mm Hg) Not applicable. Vapour Density (Air=1) Not applicable. Density (g/ml) No data. Solubility (Water) Soluble. Solubility (Other) No data. Partition Coefficient No data. Auto Ignition Point (°C) Not applicable. Decomposition Temperature (°C) Not applicable. Viscosity (mPa. s) Not applicable. Explosive properties Not applicable.

9.2 Other information Bulk density: Approximately 68 lbs/ft3 untamped, 77 lbs/ft3

Not applicable.

tamped

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity See Section: 10.3

10.2 Chemical stability This product is hygroscopic.

Revision: GHS v1.1 Ref: 01-1-1-00-000 - en -Date of Issue: 04/2013 PQUS - GHS - 3 Date Previous Issue: 5/22/2009

Page: 4 of 7



10.3 Possibility of hazardous reactions

When arc welding vessels containing aqueous solutions of this material, take care to control any explosion risk from hydrogen evolved by electrolysis. Aqueous solutions will react with aluminium, zinc, tin and their alloys evolving hydrogen gas which can form an explosive mixture with air. Can react violently if in contact with acids. Can react with sugar residues to form carbon

monoxide.

10.4 Conditions to avoid 10.5 Incompatible materials 10.6 Hazardous decomposition See Section: 10.3 See Section: 10.3

product(s)

Hydrogen

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

Ingestion Material will cause chemical burns. All symptoms of acute toxicity

are due to high alkalinity.

Oral LD50 (rat) 1152-1349 mg/kg bw

Inhalation Dust is severely irritant to the respiratory tract. All symptoms of

> acute toxicity are due to high alkalinity. Inhalation LC50 (rat) >2.06 g/m3

Skin Contact Material will cause chemical burns.

Dermal LD50 (rat) >5000 mg/kg bw

Eye Contact Material will cause chemical burns. May cause permanent

damage if eye is not immediately irrigated.

Skin corrosion/irritation Corrosive to: Skin. Serious eye damage/irritation Corrosive to: Eyes. Sensitisation Not sensitising, (LLNA)

Mutagenicity No evidence of genotoxicity. In vitro/in vivo negative. Carcinogenicity Components are not listed by IARC, NTP or OSHA as

carcinogens.

Reproductive toxicity No evidence of reproductive toxicity or developmental toxicity.

STOT - single exposure Irritating to respiratory system.

STOT - repeated exposure Not classified. NOAEL oral (rat) 227 mg/kg bw/d

Aspiration hazard Not classified Other information Not applicable.

SECTION 12: ECOLOGICAL INFORMATION

Fish (Brachydanio rerio) LC50 (96 hour) 210 mg/l 12.1 Toxicity

Aquatic invertebrates: (Daphnia magna) EC50 (48 hour) 1700

mg/l

12.2 Persistence and

degradability

Inorganic. Soluble silicates, upon dilution, rapidly depolymerise into molecular species indistinguishable from natural dissolved

Inorganic. The substance has no potential for bioaccumulation.

12.3 Bioaccumulative potential

12.4 Mobility in soil

Not applicable.

12.5 Results of PBT and vPvB

Not classified as PBT or vPvB.

assessment

12.6 Other adverse effects

The alkalinity of this material will have a local effect on

ecosystems sensitive to changes in pH.

SECTION 13: DISPOSAL CONSIDERATIONS

Revision: GHS v1.1 Ref: 01-1-1-00-000 - en -Date of Issue: 04/2013 PQUS - GHS - 3 Date Previous Issue: 5/22/2009

Page: 5 of 7



13.1 Waste treatment methods

Dispose of this material and its container to hazardous or special waste collection point. This material is classified as hazardous waste under EC Directive 2008/98/EC. This material is classified as hazardous waste under the Hazardous Waste (England and Wales) Regulations SI 2005 No. 894. This material is classified as hazardous waste under the Hazardous Waste (England and Wales) Regulations SI 2005 No. 894.

Disposed water/wet solutions containing this material are classified as RCRA hazardous waste if they exhibit the corrosive characteristic (pH greater than or equal to 12.5).

Disposal should be in accordance with local, state or national

legislation.

SECTION 14: TRANSPORT INFORMATION

14.1 UN number 3262

14.2 Proper Shipping Name Corrosive Solid, Basic, Inorganic, n.o.s. (Sodium metasilicate,

Anhydrous)

14.3 Transport hazard class(es) 14.4 Packing group П

14.5 Environmental hazards Not classified as a Marine Pollutant. Unsuitable containers: Aluminium 14.6 Special precautions for user

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

TSCA Inventory Status: Reported/Included. AICS Inventory Status: Reported/Included. DSL/NDSL Inventory Status: Reported/Included.

German Water Hazard Classification VwVwS: Product ID number 847, WGK class 1 (low hazard to water).

15.2 Chemical Safety Assessment Information available on request.

SECTION 16: OTHER INFORMATION

Data referenced in this eSDS is from company-owned information and from data legitimately accessed by PQ Corporation through membership of Industry Consortia or other agreements. This includes data relating to toxicology, ecotoxicology, DNELs, PNECs and other information in this eSDS and its annex.

This SDS was last reviewed: 04/2013

The following sections contain revisions or new statements: All sections updated to comply with Regulation (EC) No.1907/2006 (REACH) and Regulation (EC) No.1272/2008 (CLP) and their amendments.

EC Classification No. 67/548/EEC

Hazard Symbol

CORROSIVE



Risk Phrases R34: Causes burns.

R37: Irritating to respiratory system.

S1/2: Keep locked up and out of the reach of children. Safety Phrases S13: Keep away from food, drink and animal feedingstuffs.

S24/25: Avoid contact with skin and eyes.

S36/37/39: Wear suitable protective clothing, gloves and

eye/face protection.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

Revision: GHS v1.1 Ref: 01-1-1-00-000 - en -Date of Issue: 04/2013 PQUS - GHS - 3 Date Previous Issue: 5/22/2009 Page: 6 of 7



GHS Classification Skin Corr. 1B / Eye Dam. 1

> STOT SE 3 Met. Corr. 1 Danger

Signal word(s)

Hazard pictogram(s)



Hazard statement(s) H314: Causes severe skin burns and eye damage.

H335: May cause respiratory irritation.

H290: May be corrosive to metals.

Precautionary statement(s) P261: Avoid breathing dust.

> P262: Do not get in eyes, on skin, or on clothing. P280: Wear protective gloves/protective clothing/eye

protection/face protection.

P301+P330+P331: IF SWALLOWED: rinse mouth. Do NOT

induce vomiting.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. PQ Corporation gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. PQ Corporation accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

- en -

Revision: GHS v1.1 Date of Issue: 04/2013

Date Previous Issue: 5/22/2009

Ref: 01-1-1-00-000 PQUS - GHS - 3 Page: 7 of 7